

---

# Django neo-pastebin Documentation

*Release 0.1.0.dev1*

**Rodolphe Bréard**

**Sep 19, 2020**



---

## Contents

---

<b>1</b>	<b>Internationalization</b>	<b>3</b>
<b>2</b>	<b>Navigation</b>	<b>5</b>
2.1	Quickstart . . . . .	5
2.2	Configuration options . . . . .	6
2.3	Customize . . . . .	7
2.4	License . . . . .	9
<b>3</b>	<b>Indices and tables</b>	<b>11</b>



Pastebin module for Django.

---

Django neo-pastebin, also known as NPB, is a text storage module for the [Django framework](#). It is designed to be easily integrated into your website and customizable.



# CHAPTER 1

---

## Internationalization

---

Supported languages are:

- `en`: English (generic)
- `fr`: French (generic)





## 2.1 Quickstart

You can install Django neo-pastebin directly from PyPI:

```
pip install django-npb
```

### 2.1.1 Integrate with Django

Add django-npb to your INSTALLED\_APPS:

```
INSTALLED_APPS = [  
    [skipped],  
    'npb.apps.NpbConfig',  
]
```

Then add the URLs:

```
urlpatterns = [  
    [skipped],  
    path('paste/', include('npb.urls', namespace='npb')),  
]
```

If you uses internationalization, you are encouraged to add the path your i18n\_patterns instead.

### 2.1.2 Configure

To configure NPB once it is set up, see *Configuration options*.

## 2.2 Configuration options

The following configuration variables may be set in your project's settings.py file.

### 2.2.1 Common settings

#### NPB\_ALLOW\_ANONYMOUS

Define whether or not anonymous users are allowed to post. Default is “False”.

#### NPB\_DEFAULT\_EXPIRATION

Set which expiration duration is selected by default. The value is a [pytimeparse](#) duration which is set in NPB\_EXPIRATION\_LENGTH. Default is the first NPB\_EXPIRATION\_LENGTH value.

```
NPB_DEFAULT_EXPIRATION = '1d'
```

#### NPB\_DEFAULT\_EXPOSURE

Default exposure for new pastes. Must be either “public”, “unlisted” or “private”. Default is “public”.

#### NPB\_EDIT\_TOLERANCE

Set the tolerance time during which a paste can be edited without being labeled as so. Set to a negative value, it always shows the edit time. Set to a positive value, it represents the number of seconds after the creation time during which edits are not shown. Zero causes an undefined behavior. Default is 1.

#### NPB\_EXPIRATION\_LENGTH

Set the allowed expiration duration. It is a list of tuples where the first element is a [pytimeparse](#) duration (16 characters maximum) and the second one is the name to be displayed.

```
NPB_EXPIRATION_LENGTH = [
    ('15m', _('15 minutes')),
    ('1h', _('1 hour')),
    ('1d', _('1 day')),
    ('1w', _('1 week')),
    ('30d', _('30 days')),
    ('365d', _('365 days')),
    ('never', _('never')),
]
```

#### NPB\_LOGIN\_REDIRECT

If “NPB\_ALLOW\_ANONYMOUS” is “False”, define whether or not anonymous users should be redirected to the login page (“True”) or get a permission denied error (“False”). Default is “True”.

## NPB\_PASTES\_LIST\_MAX

Maximum number of posts displayed in the “recent posts” list. Set it to zero if you want to disable the list. Default is 5.

## NPB\_REPORT\_CATEGORIES

Set the list of reasons a paste can be reported to an administrator. It is a list of tuples where the first element is a short identifier (16 characters maximum) and the second one is the name to be displayed.

```
NPB_REPORT_CATEGORIES = [
    ('illicit', _('illicit content')),
    ('explicit', _('explicit content')),
    ('copyright', _('copyright infringement')),
    ('private', _('private information exposure')),
    ('other', _('other')),
]
```

## NPB\_TAB\_SIZE

Set the number of spaces needed to represent a tabulation. Default is 4.

## NPB\_X\_FORWARDED\_FOR

Defines how NPB must use the X-Forwarded-For HTTP header. The value must be one of the following:

- “none”: Do not use the header at all.
- “first”: Use the first IP listed as the end-user’s one.
- “last”: Use the last IP listed as the end-user’s one.

Default is “none”.

## 2.2.2 Development settings

### NPB\_CSS\_CLASS

Name of the generated CSS file for syntax highlighting.

## 2.3 Customize

### 2.3.1 Add fields to the forms

There is many reason to use a custom form. The most obvious one is to add your favorite captcha engine. Fortunately, it is very simple to add such custom fields.

First, you need to build the form itself by overloading one of the default one. Base it upon `npb.forms.PasteForm` or `npb.forms.ReportForm` depending on which form you want to extend.

```
from django.utils.translation import gettext_lazy as _
from npb.forms import PasteForm, ReportForm
from django import forms

class MyCustomForm(PasteForm):
    my_field = forms.CharField(
        label=_('My field'),
        max_length=128,
    )
```

Once your form is ready, pass it to the view.

```
from django.urls import path
from npb import views as npb_views
from .forms import MyCustomForm

urlpatterns = [
    path(
        '',
        npb_views.CreatePasteView.as_view(form_class=MyCustomForm),
        name='index'
    ),
]
```

## 2.3.2 Editing the style

The simplest and more powerful way to edit the style is to [override templates](#). The following templates are open to overriding:

### npb/base.html

This template contains the HTML page's structure. It defines the following empty blocks that will be extended by other templates:

- `headers`: A place to add extra HTML headers.
- `title`: The page's title.
- `content`: The page's content.

It also displays [Django's messages](#) and, if activated, recent pastes.

### npb/paste\_detail.html

This template is used to render a specific paste. For this purpose, it uses the `paste` variable. Please refer to the `Paste` object in order to list its available properties.

### npb/paste\_form.html

This template is where the new past form is rendered. It uses the `form` variable which is by default a `npb.PasteForm` object.

### `npb/report_form.html`

Same as the new paste form but for a new report. The default associated form object is a `npb.ReportForm`.

### `recent_pastes`

In your templates, you can load `recent_pastes` to have access to the following tags:

- `recent_pastes_activated`: True if the recent pastes list is activated, False otherwise.
- `recent_pastes`: Return an iterator over the most recent pastes.

## 2.4 License

This software is governed by the [CeCILL-B](http://www.cecill.info) license under French law and abiding by the rules of distribution of free software. You can use, modify and/ or redistribute the software under the terms of the [CeCILL-B](http://www.cecill.info) license as circulated by CEA, CNRS and INRIA at the following URL “<http://www.cecill.info>”.



## CHAPTER 3

---

### Indices and tables

---

- `genindex`